

50Hz

Crass Flow & Counter flow & wheel

2021





#### MULTI STAGE EVAPORATIVE COOLING



8 -14 (U) 14 (U) 単語 ł R. No 200 daland du on 86 10 CIII. Special Public places Commercial, Office, Hospital, Restauran Coffee shop & Etc . 

A

1

-





General	3
Introduction	3
Flexibility	4
Modular Design	4
Outstanding Features	7
Certificate/quality	8
Customized Solution For Indoor Air Quality	9
Air Handling Unit selection Software	10
Standard Selection	11
Range	13
Nomenclature	13
Airflow rate coverage range of models based on velocity	14
Performance Report from Selection Software	16
Drawing View from Selection Software	17
AHU Air handling Unit Details	18
Ultimate casing design and construction	
Frame and panel	19
Access Door	23
Mixing Box Section	
Mixing box	24
• Damper	24
Filters	
Flat Filters	25
Bag Filters	25
HEPA Filters	26
Optional Components	26
Filter standards	27
Fan section	
• Fans	29
Motors	30
Fan & Motor Assembly	30
Customized Fan Assembly	30
Fan Mounting in the Different Orientations	31

### **Coil Section**

Cooling & Heating Coils	32
Moisture Eliminator	33
Optional Features of Coil	34
UV Light	34
Electric Heater	34
Heat recovery	35
Control equipment	
Variable Frequency Drive	35
Control valve	35
Damper actuator	36
Steam Humidifier	36
Typical Wiring Diagram	37
Notes	38

### GENERAL

Knowledge of our customer's needs, European regulations (Eurovent) and local regulations in different countries, as well as the long-term experience of our team has enabled us to develop and launch a new generation of air-handling units. This new generation features not only significantly better parameters but also even greater reliability. New Eco cooler air-handling units significantly enhance the quality level of RIC air-handling units and set a new, higher standard.

ECO COOLER air handling units allow offering the customer reliable and quality equipment which technical parameters allow to create not only comfortable conditions of a microclimate in various premises, but also to correspond to modern ecological and energy efficient requirements.

### INTRODUCTION

Increasing environmental pollution, the quality of air that we breathe is of vital importance. Air-handling units are designed for essential features and sensitive installations of high-demanding air conditioning applications like hospitals, shopping mall, oil refineries, industries, electronic facilities, etc. The purpose of this catalogue is to guide the consulting engineers in the preliminary selection of ECO COOLER Air Handling Units. However, if required, our local sales office will assist to provide a computerized selection to confirm or complete your preliminary selection.

## FLEXIBILITY

ECO COOLER AHUS offer the ultimate in dimensional, material, and component flexibility. ECO COOLER AHUS have the same appeal for both "standard" and "custom" markets. How an air-handling unit is designed and built determines how well it performs.

#### **Engineering Flexibility**

- Variety of case sizes.
- Material and component flexibility.
- Variable sized inlet and discharge openings.
- stacked and custom configurations.
- Panels are individually removable without affecting structural integrity.

#### **Dimensional Flexibility**

We can design our AHUs to fit the application and the space. With up to 30 case sizes and hundreds of cross-sectional possibilities, we can design the best match for your application.

#### **Material Flexibility**

A complete line of construction materials are available, including galvanized steel, aluminum, painted steel, stainless steel, and more. ECO COOLER AHUs can handle a multitude of environments, from the most benign to the most corrosive.

### MODULAR DESIGN

Based on modularity and a flexible approach, the unique ECO COOLER Air Handling Unit allows you to choose the exact level of functionality required by a specific project. The modules are joined together and with all the functionalities contained in just one unit. Installation and maintenance, therefore, have never been seen so easier.

# **RELIABLE BRAND**





# **OUTSTANDING FEATURES**

#### **Heat Recovery Unit**

- 30 different models of units within a range of airflow rate 1000-60000 CFM in two categories of Hygienic and Non-Hygienic types.
- The procedure of design, manufacturing, and providing equipment are in accordance with VDI 6022
- The unit casing is made up of panels and frame. Panel construction is a double skin sandwich panel with 50-mm injected polyurethane foam with a density of 40 kg/m<sup>3</sup> in accordance with DIN EN 13053-6.2. In Hygienic models, panel inner skin is made of Stainless steel and in non-hygienic models is made of galvanized steel sheet coated by polyester electrostatic powder. Panel outer skin is made of galvanized steel sheet coated by PVC with 200-micron thickness. The frame is built by PROLAM aluminum profile certified by DIN EN 13779-8.2. The frame inner side surface is curved and smooth to avoid contamination deposition.
- Construction frame classifications in accordance with EN1886 are:
  - 0 Mechanical strength (–1,000 Pa): D1 (M)
  - Mechanical strength (+1,000 Pa): D1 (M) 0
  - Casing air leakage (-400 Pa): L1 (M) 0
  - Casing air leakage (+700 Pa): L1 (M) 0
  - Thermal transmittance class: T2 0 TB1
  - Thermal bridging class: 0
  - Filter class: 0



F9

# OUTSTANDING FEATURES

#### **Heat Recovery Unit**

- The access door is equipped with an adjustable polyamide lock and hinge and sealing gasket suitable for negative and positive pressure conditions in accordance with VDI 3803/1-5.1.
- 40-cm Minimum width of the access door to access and inspect all sections of the unit in accordance with DIN EN 13053-6.2.
- Fan type: Low-noise forward double-inlet centrifugal or plug type manufactured by Nicotra-Gebhardt with manufacturing standard DIN 19464-6.5.10 and Testing standard AMCA 210.
- With the fan and motor assembly mounted on a common base with shock absorber and the fan outlet isolated from the casing by a flexible connection and completely separated from moving parts. Moreover, the forward or plug fan may be selected according to the total air pressure drop and volume.
- Fan motor: The motor features IP55 and type F insulation.
- Dampers: made of aluminum airfoil-shaped profile with fibered polypropylene gears, easy installation of the motor in accordance with **VDI 3803/1-5.2.9**.
- Cooling and heating coils: tube material is copper and fin material is copper or aluminum. Fin arrangement is a V-waffled louvered enhanced type. The coating can be blue, gold, Here site or hydrophilic to enhance the resistance against corrosion and humid and acidic environments in accordance with **DIN EN 13053-6.4.4**.
- Filters of various filtering levels are available ranging from primary filters (Panel type, efficiency: G2-G4), to medium filters (Bag type, efficiency: M6 F9), and to high filters (H13-H14-U15). Some special filters such as active carbon filters and UV lamps can also be provided. Filters are tested in accordance with DIN EN 779 and installed in accordance with DIN EN 13053-6.9.2.
- Drain pan: made of painted galvanized steel or stainless-steel sheet. All sections of the unit are equipped with the drain pan.



### Certificates / quality

#### **EC Directives**

CE

With the CE mark, the manufacturer declares that, pursuant to EU Regulation 765/2008. the product complies with the applicable requirements laid down in the Community harmonization legislation.





VDI guideline for hygienic engineering, design and maintenance of air handling equipment. Guideline VDI 6022 largely corresponds to Swiss standard SWKI VA 104-1 and Austrian standard H 6021.





These products comply with Directive 2004/108/EC Electrical compatibility of electrical and electronic products TS EN 61000-6-2:2019 IEC 61000-6-2:2016 RLV TS EN 61000-6-2:2019 IEC 61000-6-2:2018 RLV

ISO 9001 ISO 14001



Certification International Standardization by the Organization (ISO) ensures that an organization can consistently deliver a product or service that meets the customer's contractual requirements by following documented processes. The ISO 9001 quality assurance model establishes the requirements for an organization whose business processes range from design and development to production.





**Good Manufacturing Practice (GMP)** is a system for ensuring that products are consistently produced and controlled according to quality standards. It is designed to minimize the risks involved in any production that cannot be eliminated through testing the final product.

# CUSTOMIZED SOLUTION FOR INDOOR AIR QUALITY

#### **Customized Applications Include:**

- Flexible Cabinet Sizing
- Galvanized, Aluminum or Stainless-Steel Panels with the various thickness
- such as 1.0, 1.2 & 1.6
- Inner Painted GI Panels.
- Selection of Drain Pan Materials.
- Mixing Boxes / Economizers.
- Multiple Coil Section Depths.
- Integral face and By-Pass Dampers.
- Variety of fans Belt or Direct Drive, Forward or Backward curved or Airfoil, Plug Fans.
- Motors Standard and Energy Efficient (IE1-IE2-IE3)
- Humidifier and De-Humidifier sections.
- Filters Flat Filters, Bag Filters, HEPA Filters
- Digital Controls
- Optional Accessories View Port, Hinge Door, Lights, etc.



	HEAT RECOVERY UNIT																			
	A	в	с	D	E	F	G	н	1	J	к	L	м	N	ο	Р	Q	R	s	т
Section	Silencer	Plenum Box	Return Fan	Heat Recovery	Prefilter	Bag Filter M4/M6	Bag Filter F7/F9	Fan Fixed Door	Supplyn Fan	Preheater	Coil Service Door	Electrical Coil / Water Heating Coil	Humidifier	Cooling Coil	Coil Service Door	DX Coil	UV Lamp	Bag Filter F9	Carbon Active Filter	HEPA / ULPA Filter H1 /U15
Dimension (mm)	1000	400	1000	2000	200	400	800	300	200	300	500	300	500	400	500	400	500	200	400	200

# CUSTOMIZED SOLUTION FOR INDOOR AIR QUALITY



	HEAT RECOVERY UNITE																		
	A	в	с	D	E	F	G	н	I	J	к	L	м	N	ο	Ρ	Q	R	s
Section	Carbon Active Filter	HEPA Filter H13	Silencer	Supply Fan	Fan Fixed Door	Humidifier	Electrical Heating Coil	Cooling & Heating Coil	Heat Recovery	Plenum Box	Fan Fixed Door	Exhaust Fan	Silencer	Prefilter	Bag Filter F9	HEPA Filter H13	Plenum Box	Bag Filter F9	Prefilter
Dimension (mm)	400	400	1000	700	300	500	300	400	1200	400	300	700	1000	700	400	400	400	200	700

# AIR HANDLING UNIT SELECTION SOFTWARE

For selecting air handling units, we use the multi language selection program. AHU SELECTION is the powerful software package developed to offer a quick and comprehensive service for the customer, in order to make the proper technical choice and economic evaluation of each AHU. It is a complete tool that can configure any type of product and respond exactly to the strictest design needs. The software is an excellent tool for sales engineers, project designers of air handling unit system. The result is a comprehensive economic offer including all the technical data and drawings, the psychometric diagram with the fans' performance curves. Besides the calculations the program also allows you to create the sketches that can be exported to Auto cad.

All the units are designed and developed with special attention to achieve high efficiency of coils, filters & motors. Case sizes are offered in two categories A,B for hygienic applications and C,D,E for non-hygienic applications



# STANDARD SELECTION

# Air Handling Unit series A , B

	Nominal air flow		Internal di	imensions	External d	imensions
Model	rate	Filter arrangement	(m	m)	(m	m)
	[m³/h]		Width	Height	Width	Height
2 000	4 250		616	616	728	728
3 000	6 375		921	616	1033	728
4 000	8 500		1226	612	1338	724
4 500	9 562		921	921	1033	1033
5 000	10 625		1531	616	1643	728
6 000	12 750		1226	921	1338	1033
7 500	15 935		1531	921	1643	1033
8 000	17 000		1226	1226	1338	1338
9 000	19 125		1836	921	1948	1033
10 000	21 250		1531	1226	1643	1338
12 000	25 500		1836	1226	1948	1338
12 500	26 562		1531	1592	1643	1704
14 000	29 750		2141	1226	2253	1338
15 000	31 875		1836	1592	1948	1704
16 000	34 000		2446	1226	2558	1338
17 500	37 185		2141	1592	2253	1704
18 000	38 250		1836	1897	1948	2009
20 000	42 500		2446	1592	2558	1704
21 000	44 625		2141	1897	2253	2009
24 000	51 000		2446	1897	2558	2009
25 000	53 125		3056	1592	3168	1704
28 000	59 500		2446	2233	2558	2345
30 000	63 750		3056	1897	3168	2009
32 000	68 000		2446	2538	2558	2650
40 000	85 000		3056	2538	3168	2650
48 000	102 000		3666	2538	3778	2650
56 000	119 000		4276	2538	4388	2650

# STANDARD SELECTION

# Air Handling Unit series C , D

	Nominal air flow		Internal di	mensions	External d	imensions
Model	rate	Filter arrangement	(m	m)	(m	m)
	[m³/h]		Width	Height	Width	Height
2 000	4 250		592	660	704	772
3 000	6 375		880	660	992	772
4 000	8 500		1185	660	1297	772
4 500	9 562		880	977	992	1089
5 000	10 625		1472	660	1584	772
6 000	12 750		1185	977	1297	1089
7 500	15 935		1472	977	1584	1089
8 000	17 000		1185	1282	1297	1394
9 000	19 125		1777	977	1889	1089
10 000	21 250		1472	1282	1584	1394
12 000	25 500		1777	1282	1889	1394
12 500	26 562		1472	1600	1584	1712
14 000	29 750		2064	1282	2176	1394
15 000	31 875		2064	1600	2176	1712
16 000	34 000		2368	1282	2480	1394
17 500	37 185		2064	1600	2176	1712
18 000	38 250		1777	1911	1889	2023
20 000	42 500		2368	1600	2480	1712
21 000	44 625		2064	1911	2176	2023
24 000	51 000		2368	1911	2480	2023
25 000	53 125		2960	1600	3072	1712
28 000	59 500		2368	2235	2480	2347
30 000	63 750		2960	1911	3072	2023
32 000	68 000		2368	2540	2480	2652
40 000	85 000		2960	2540	3072	2652
48 000	102 000		3552	2540	3664	2652
56 000	119 000		4144	2540	4256	2652

### RANGE

A wide standard range covers air flow rates from 1 000 cfm up to 60 000 cfm, with the possibility to choose the most appropriate transverse velocity, depending on the treatment required. In addition, with the same air flow, the flow section (width x height) can be adapted to the dimensional constraints of the installation. All sizes are modularly constructed to facilitate transport and easy assembly on site. With the absence of any welding points the AHU units, on request, can be supplied completely dismantled to allow assembly directly on site.

### NOMENCLATURE



# Airflow rate coverage range of models based on velocity

				Velocity*			Internal d	imensions	External d	imensions
Model	Nominal air flow			m/s			(m	ım)	(m	m)
	rate	1.5	2	2.5	3	3.5	Width	Height	Width	Height
2000	4 250	2082	2776	3471	4165	4859	616	616	720	720
3000	6 375	3113	4151	5189	6227	7264	921	616	1022	720
4000	8 500	4117	5490	6862	8235	9607	1226	612	1000	724
4500	9 562	4655	6206	7758	9310	10861	921	921	1022	1022
5000	10 625	5175	6900	8626	10351	12076	1531	616	1642	720
6000	12 750	6196	8262	10327	12393	14458	1226	921	1045	1022
7500	15 935	7738	10317	12896	15476	18055	1531	921	16/13	1033
8000	17 000	8248	10998	13747	16497	19246	1226	1226	1338	1338
9000	19 125	9279	12372	15465	18559	21652	1836	921	1948	1033
10 000	21 250	10300	13734	17167	20601	24034	1531	1226	1643	1338
12 000	25 500	12352	16470	20587	24704	28822	1836	1226	1948	1338
12 500	26 500	13375	17834	22292	26750	31209	1531	1592	1643	1704
14 000	29 750	14404	19206	24007	28808	33610	2141	1226	2253	1338
15 000	31 875	16040	21386	26733	32080	37426	1836	1592	1948	1704
16 000	34 000	16456	21942	27427	32912	38398	2446	1226	2558	1338
17 500	37 185	18704	24939	31174	37409	43643	2141	1592	2253	1704
18 000	38 250	19113	25484	31855	38225	44596	1836	1897	1948	2009
20 000	42 500	21369	28492	35615	42738	49861	2446	1592	2558	1704
21 000	44 625	22288	29717	37146	44576	52005	2141	1897	2253	2009
24 000	51 000	25463	33950	42438	50926	59413	2446	1897	2558	2009
25 000	53 125	26698	35597	44497	53396	62295	3056	1592	3168	1704
28 000	59 500	29973	39964	49955	59946	69937	2446	2233	2558	2345
30 000	63 750	31813	42417	53021	63626	74230	3056	1897	3168	2009
32 000	68 000	34067	45422	56778	68133	79489	2446	2538	2558	2650
40 000	85 000	42563	56750	70938	85125	99313	3056	2538	3168	2650
48 000	102 000	51058	68078	85097	102117	119136	3666	2538	3778	2650
56 000	119 000	59554	79405	99257	119108	138960	4276	2538	4388	2650

\* Air velocity is based on internal dimension of models. For coil face velocity, the air flow rate is almost 10% smaller than one presented in the table.

# MODEL SELECTION CHART

				Velocity*			Internal d	imensions	External di	imensions
	Nominal			FPM			(m	m)	(m	m)
Model	air flow rate [CFM]	300	400	500 (CFM)	600	700	Width	Height	Width	Height
2000	2500	1225	1633	2041	2450	2858	616	616	728	728
3000	3750	1831	2442	3052	3663	4273	921	616	1033	728
4000	5000	2422	3229	4037	4844	5651	1226	612	1338	724
4500	5625	2738	3651	4564	5476	6389	921	921	1033	1033
5000	6250	3044	4059	5074	6089	7103	1531	616	1643	728
6000	7500	3645	4860	6075	7290	8505	1226	921	1338	1033
7500	9250	4552	6069	7586	9103	10621	1531	921	1643	1033
8000	10000	4852	6469	8087	9704	11321	1226	1226	1338	1338
9000	11250	5458	7278	9097	10917	12736	1836	921	1948	1033
10 000	12500	6059	8079	10098	12118	14138	1531	1226	1643	1338
12 000	15000	7266	9688	12110	14532	16954	1836	1226	1948	1338
12 500	15500	7868	10490	13113	15736	18358	1531	1592	1643	1704
14 000	17500	8473	11297	14122	16946	19770	2141	1226	2253	1338
15 000	18750	9435	12580	15725	18870	22015	1836	1592	1948	1704
16 000	20000	9680	12907	16134	19360	22587	2446	1226	2558	1338
17 500	21874	11003	14670	18338	22005	25673	2141	1592	2253	1704
18 000	22500	11243	14990	18738	22486	26233	1836	1897	1948	2009
20 000	25000	12570	16760	20950	25140	29330	2446	1592	2558	1704
21 000	26250	13110	17481	21851	26221	30591	2141	1897	2253	2009
24 000	30000	14978	19971	24964	29956	34949	2446	1897	2558	2009
25 000	31250	15705	20940	26175	31409	36644	3056	1592	3168	1704
28 000	35000	17631	23508	29385	35262	41139	2446	2233	2558	2345
30 000	37500	18713	24951	31189	37427	43665	3056	1897	3168	2009
32 000	40000	20039	26719	33399	40079	46758	2446	2538	2558	2650
40 000	50000	25037	33382	41728	50074	58419	3056	2538	3168	2650
47 000	60000	30034	40046	50057	60069	70080	3666	2538	3778	2650
48 000	70000	35032	46709	58386	70064	81741	4276	2538	4388	2650

\* Air velocity is based on internal dimension of models. For coil face velocity, the air flow rate is almost 10% smaller than one presented in the table.

# PERFORMANCE REPORT FROM SELECTION SOFTWARE



# DRAWING VIEW FROM SELECTION SOFTWARE





# **AIR HANDLING UNIT DETAILS**







# ULTIMATE CASING DESIGN AND CONSTRUCTION

#### Frame & Panels

THERMAL BREAK SYSTEM 50 WITH "PANEL STOP" PROFILES



#### **DESCRIPTION:**

The new thermal break system guarantees a high thermal insulation thanks to the use of special shaped polyamide bars 25 mm long. One of the peculiarities of this system is the half omega profile that allows the union of two or more units ensuring the thermal bridging between them. This profile thanks to its 40 mm section is very solid. The "panel stop" profiles hold the panels without the use of screws: the system could fit traditional panels made with double steel bended sheet and also sandwich panels that are cheaper and are able to provide a better insulation than traditional ones.

The use of a patented gasket system ensures smooth internal surfaces - so the AHU is easily cleanable - and a perfect air tightness inside the unit. Moreover, the interior of the frame has been designed with a radius shape and nylon rounded corners in order to simplify the maintenance of cleanliness inside the unit. To improve the mechanical and air tightness properties of the frame, the nylon and omega joint corner have special grooves for screws that fasten together the aluminum profile with the plastic components. Furthermore, the screws are hidden by nylon caps that prevent the formation of dust and dirt near the head of the screws.



# ULTIMATE CASING DESIGN AND CONSTRUCTION

#### Frame & Panels

Summary table of the results obtained from specific software:

PROFILE TYPE	Ti	t s-max	ta	kb	Thermal Class
System 60/50 – <u>P 160/50 PS TB IR</u>	12	14.52	45	<mark>0,92</mark>	TB1
System 60/50 – <u>P 260/50 PS TB</u>	12	14.29	45	<mark>0,93</mark>	TB1
System 60/50 – <u>P 260/50_2 PS TB</u>	12	14.75	45	<mark>0,92</mark>	TB1

#### TRIALS AND TESTS CARRIED OUT IN THE LABORATORY

The high thermal insulation class of this thermal brake system has been confirmed by trials and tests performed in the laboratory on an AHU assembled with corner post and omega thermal break profiles, panel stop profiles and patented gasket system. The tables below show the test results that completely meet thermal insulation specifications in compliance with EN 1886.

THERMAL PERFORMANCE	EN 1886	REFERENCE VALUES	RESULT	THERMAL CLASS
THERMAL TRANSMITTANCE	Class T1 Class T2 Class T3 Class T4 Class T5	$U \le 0,5$ 0,5 < U $\le 1,0$ 1,0 < U $\le 1,4$ 1,4 < U $\le 2,0$ No requirements	<u>0,43</u>	CLASS T 1
THERMAL BRIDGING	Class TB1 Class TB2 Class TB3 Class TB4 Class TB5	$0,75 < k_b < 1,00$ $0,60 < k_b \le 0,75$ $0,45 < k_b \le 0,60$ $0,30 < k_b \le 0,45$ No requirements	<mark>0,81</mark>	CLASS TB 1



# ULTIMATE CASING DESIGN AND CONSTRUCTION

#### Frame & Panels

#### AIR TIGHTNESS FEATURES THERMAL BREAK SYSTEM 60/50 WITH "PANEL STOP" PROFILES

The tests carried out on a "model box" have highlighted the excellent air tightness of the AHU examined. The results obtained are shown in the tables below.

	- 400 Pa	Class L1 Class L2 Class L3	≤ 0,15 (I * s <sup>-1</sup> * m <sup>-2</sup> ) ≤ 0,44 (I * s <sup>-1</sup> * m <sup>-2</sup> ) ≤ 1,32 (I * s <sup>-1</sup> * m <sup>-2</sup> )	0,13 = CLASS L1
CASING AIR LEAKAGE	+ 700 Pa	Class L1 Class L2 Class L3	≤ 0,22 (I * s <sup>-1</sup> * m <sup>-2</sup> ) ≤ 0,63 (I * s <sup>-1</sup> * m <sup>-2</sup> ) ≤ 1,9 (I * s <sup>-1</sup> * m <sup>-2</sup> )	0,19 = CLASS L1

MECHANICAL STRENGTH	TEST PRESSURE	EN 1886	REFERENCE VALUES	RESULT
DEFLECTION	-1000 Pa	Class D1 Class D2 Class D3	≤ 4 mm * m <sup>-1</sup> 10 mm * m <sup>-1</sup> >10 mm * m <sup>-1</sup>	0,51 = CLASS D1

The *panel stop profiles* fix the panel without using screws and *guarantee air tightness* around the perimeter of the frame.



The gasket adheres perfectly to the panel and it creates a smooth inner surface between profiles and panels.

### **Access Doors**

Handle / Hinges

Lockable handle



#### **Explanation**

The doors for inspection and internal service can be provided with either outward opening or inward opening for pressurized sections. There are solutions with hinges to allow left or right openings and cam handles to lock and open the door Or even the total removal of the door.

**Inspection Window** 



#### Explanation

The portholes are double-wall type made of polycarbonate and with sealing gaskets. The fastening system with locking screws that only enter the polycarbonate structure (and therefore not into the sandwich panel) and the continuous internalexternal gasket, prevents the formation of condensation and ensures maximum sealing.

### MIXING BOX SECTION



#### Construction

Intake/mixing box is available with damper section based on the project Requirement.

#### Construction

Aluminum extruded frames (1.8 mm thick), with aero foil design blades. Special gaskets are fixed at the blade edges to avoid the leakage. Gear wheels are made from polypropylene material. Galvanized steel shaft 12mm x 12 mm (square) with aluminum handles for opening and closing the damper. Damper working condition is - 20°c / +80°c, tested and certified by TUV Sud / Munich.

#### Function

Dampers are used to control or to shut down the air moving in or out of the air handling system. Dampers can be operated manually or can be supplied or fitted with actuators to regulate the flow.

- Airfoil design
- Opposed blade

•Fitted with neoprene gasket in between blades to reduce leakage

•316L Stainless steel dampers (Optional)

#### Dampers



### FILTERS

Always taking special care, during the configuration of the unit, to the position of the filters in the airflow, in order to maximize them effectiveness. All filters are mounted on aluminum filter fixing frames, provided with a seal to ensure effective filtration efficiency.

#### **Flat Filters**



#### **Explanation**

Polyester fiber media panel filters, class G3 supplied as standard. Aluminum washable filters, class G2 will be provided upon customer request.

#### **Bag Filters**



#### Explanation

Synthetic or glass-fiber media bag filters, class starts from M5 to M6, & F7 to F9 fixed in aluminum frame with gaskets to avoid air bypass. Bag Filters are available on two different lengths, 380mm long is standard version and 600 mm long as an optional. Filters having big filtration surface area will give longer life. Filters are fastened by clamping mechanism which secures tightness and simplifies filter replacement procedure.

### FILTERS

Always taking special care, during the configuration of the unit, to the position of the filters in the airflow, in order to maximize them effectiveness. All filters are mounted on aluminum filter fixing frames, provided with a seal to ensure effective filtration efficiency.

#### **HEPA Filters**



#### Explanation

HEPA Filters of H13 & H14 class have excellent air cleaning efficiency of their advanced design. A rigid media with Aluminum or PVC Separators provides high efficiency of air filtration at the lowest possible resistance. Rated in accordance with EN1822.

#### **Pressure switch**





#### **Optional Components**

- Stainless steel filter frame
- Differential pressure switch
- Inclined gauge manometer
- Magnehelic gauge with contact 0-2500 Pa
- Magnehelic gauge without contact 0 -2500 Pa





### **FILTER** standards

The determination od the filter performance of particulate filters for general room air technology has been described by the industry standard EN779:2012.

EN 779:2012 standard is a certification programmer applicable to air filter elements rated and sold as "Medium and Fine Class M5,M6,and F7 to F9"

For coarse filters, the filter effect is evaluated by measuring the initial gravimetric arrestance when challenging the filter with synthetic test dust using ASHRAE-test dust.

For fine filters, the filter effect is evaluated by measuring the efficiency against 0.4 micron DEHS droplets, the classification of classes defined in EN779:2012 is shown in Table 1.

Classification of Coarse, Medium and Fine filters according to EN 799:2012							
Type of filter	EN 779:212	Average arrestance with	e Average efficiency with of 0.4 μm particles oust (Em%)	Final pressure	Medium efficiency 0.4 μm (%)		
51	Efficiency Class	synthetic Dust (Am%)		drop (Pa)			
Coarse filters	G1	50≤Am≤65	-	250			
	G2	65≤Am≤80	-	250			
	G3	80≤Am≤90	-	250			
	G4	90≤Am	-	250			
Medium	M5	- 40≤Em≤60		450			
filters	M6	-	- 250 40≤Em≤60 450 60≤Em≤80 450	450			
Fine filters	F7	-	80≤Em≤90	450	35		
	F8	-	90≤Em≤95	450	55		
	F9	-	95≤Em	450	70		

ISO 16890 is the new global standards for air filter testing and classification and replaces the existing EN779:2012 standard. This new standard represents a major turning point in the evaluation of filter efficiency.



ISO 16890 classification are based on where particles are deposited in the human lung.

The new international ISO 16890 standard defines four new filter groups based on dust particle size



ISO 16890 filter test procedures are considering the range from 0,3µm - 10µm

### **FILTER standards**

The essential feature of the new test is the broad particle size distribution. The new ISO 16890 standard focuses on the filtration efficiency of different sizes of fine particles. It is listed as below 4 different filter classification:

- ISO Coarse (assessment of the separation of ISO A2 dust
- ISO PM10: particle size ≤10 µm
- ISO PM2.5: particle size  $\leq$ 2.5 µm
- ISO PM1: particle size  $\leq 1 \ \mu m$

ISO 16890 is therefore a much more concrete standard on the subject than the theoretical EN779:2012 which used particle of 0.4 micron to measure the effectiveness of filters from M5 to F9. With the new ISO 16890 filter standard, filtration effectiveness are determined based on the different PM1, PM2.5 and PM 10 fine particle sizes. The same parameters are used as those deployed by the World Organization (WHO) or the Federal Environmental Agency.

Filter groups according to ISO 16890						
Filter Class	Efficiency range	Particle Size (µm)	Examples for fine dust			
ISO ePM1	ePM1,min ≥ 50%	0.3 μm ≤x≤ 1.0 μm	Ultra fine dust with a diameter of less than 1 $\mu m$ : Viruses, Bacteria, nanoparticles, soot (from fossil fuels)			
ISO ePM2.5	ePM2.5,min ≥ 50%	0.3 μm ≤x≤ 2.5 μm	Fine dust with a diameter of less than 2.5 $\mu\text{m}$ : pollen, rock dust from field cultivation			
ISO ePM10	ePM10 ≥ 50%	0.3 μm ≤x≤ 10.0 μm	Fine dust with a diameter of less than 10 $\mu m$ : Bacteria, fungal and molds pores, pollen, toner dust			
ISO Coarse	ePM10 ≤ 50%	0.3 μm ≤x≤ 10.0 μm	Visible coarse dust: sand, hair sand leaves, lint, air born seed lings,etc.			

The testing and evaluation procedures of ISO 16890 and EN 779 differ greatly. Therefore use of tables or calculations which claim to convert G1-F9 filter classes into ISO filter groups cannot be recommended. Between EN779 and ISO 16890 there are similarities as below:

Filter Class	ISO 16890-Average Efficiency					
EN 779:2012	ePM1	ePM2.5	ePM10	Coarse		
G2	-	-	-	30%-50%		
G3	-	-	-	55%-75%		
G4	-	-	-	80%95%		
M5	5%-35%	10%-45%	40%-70%	-		
M6	10%-40%	20%-50%	60%80%	-		
F7	40%-65%	65%75%	80-90%	-		
F8	65%-90%	75%95%	90%100%	-		
F9	80%-90%	85%95%	90%-100%	-		

# FAN SECTION

Rigid Fan Assembly with Standard AHU Components

#### Fans





#### AMCA CENTIFIED RETIRGS PERCENTION MICROSTICUT MICROSTI

#### **EXPLANATION**

- Centrifugal Forward Curved DIDW Fans are manufactured in Galvanized Steel Sheet. The impellers manufactured in galvanized sheet steel statically and dynamically balanced, in accordance with VDI 2060 and ISO 1940/1, grade G 6, 3. Impeller diameters are in series R20 according to DIN 323.
- Shafts are manufactured from high quality steel Centrifugal Backward Curved DIDW/AEROFOIL Fans are manufactured in Galvanized Steel Sheet with Structurally reinforced housing.
- The Impeller is manufactured in Glass reinforced polyamid with Backward Curved and balanced, both statically and dynamically, to an accuracy grade of G = 6,3 in accordance to DIN ISO 1940-1 (VDI 2060).
- Shafts are manufactured from high quality steel, they are precision ground and polished.
- The Plug type Plenum Fan is a Direct Driven Single Inlet Centrifugal Fan without Volute Fan Casing.
- The Impellers are Manufactured in steel, with either backward curved or backward curved airfoil blades and painted finish.
- The Impellers are directly mounted on the Shaft end of Single Speed Motor.



### FAN SECTION

Rigid Fan Assembly with Standard AHU Components

### **Motors**



#### Explanation

- Motors protection is ensured by an enclosed fan cooled type class F insulation to IP55.
- Fans are delivered with the single speed motors.
- Control Box is mounted at the top.
- Optional: Eff1 (IE2) or EFF2 (IE1)

#### Fan & Motor Assembly



#### Construction

Entire fan assembly fixed on a separate galvanized steel frame isolated from the unit structure by rubber anti-vibration mounts (spring as an option). This arrangements guarantee that the AHU does not transmit vibrations to any flat surface on which it is installed

#### EC Fan



#### Construction

Realistic performance specifications, as the performance data of the entire fan is continuously measured by means of the components: high performance impeller, GreenTech EC motor and control electronics.

## FAN SECTION

#### Rigid Fan Assembly with Standard AHU Components



#### Customized Fan Assembly Include:

The customized Fan assembly design includes the following optional features:

- Stand by motors for 24 x 7 operations
- Double fan with double motor
- Spark proof fans
- Inlet guide vanes for VAV control
- Explosion proof motors
- Stainless steel shaft fans
- Extended lubrication fittings
- Fans with drain plug
- Fans with inspection window
- Bulk Head light

#### Fan Mounting in the Different Orientation:



Sizes 315 and 560 mm



Parallel mode of fans

# COIL SECTION

#### Cooling & Heating Coil



#### Construction

- Computer selected Cooling and heating coils to achieve the optimum thermal and psychometric efficiency with low pressure drops of water and Air.
- Variety of coils including water, direct expansion (R22, R134a, R407C and R410A) and steam coil are available to meet wide range of application requirements.
- Coils comply with AHRI 410 standard.
- Mechanically bonded to aluminum fins, copper tubes with Aluminum End sheets arranged in a stagger form in the direction of air flow.
- Headers are made from copper. Air vents fixed at top of the coil headers. Coil's leak tested at 350 psi air pressure. Cooling coil assembly is mounted on the top of sliding rails for easy with drawl. Entire coil section is covered by stainless steel drain pan with inclined angle design. Drain pans are insulated against condensation with MPT drain connection as a standard.



# COIL SECTION

#### **Moisture Eliminator**



Construction

#### **Explanation**

Moisture eliminators fixed after the cooling coil when velocity exceeds 2.5 m/s.

#### **Optional Features of Coil:**

The customized coil design includes the following optional features.

- Copper or Blue fins.
- Anti corrosive protection coating for fins
- Stainless steel sliding rails.
- Stainless steel coil casing.
- Galvanized (painted) drain pans
- Coil with by-pass dampers.
- U.V. Lights for high level of air purification and deodorization.

The patented Coil Clean IL UV Systems are designed to prevent and destroy mold and other microbial growth from growing on the evaporator coil and surrounding areas. The benefits include eliminating biological "blow-off" of bacteria, viruses, spores and odors into the building while maintaining a clean coil eliminating the need for conventional coil cleaning. Typically, bio-film coats the coil reducing heat transfer negatively impacting coil efficiencies, the Coil Clean IL maintains a clean coil maximizing system performance enabling the coil to work at optimum efficiency saving energy. Equipped with High-Intensity 19 mm. Quartz UVC Lamps and High-Output Electronic Ballasts paired to Anodized Aluminum Parabolic Reflectors make the Coil Clean Series incredibly effective. By using Anodized Aluminum Parabolic Reflectors, UV Coil Clean Purifiers are able to direct virtually all the UV Energy onto the coil without losing UV on the back-end top and bottom of the UV Lamp. The Reflector also protects plastics and wiring from destructive UV rays. The Coil Clean Parabolic Reflector maximizes UV energy much the same way a flashlight or a car's headlight uses a reflector to direct the UV energy where it is needed most, the coil. Using any other UV Lamp / Emitter will result in losing more than half the UV energy.

#### LED Status Display

Each Coil Clean IL system includes an LED Status Display incorporated into each Ballast.The 3 color LED notifies the end-user on the status of the UV system and when the UV Lamp needs to be replaced.

#### **Dry Contacts**

Each UV Coil Clean IL system includes a pair of Dry Contacts (NO & NC). Dry Contacts make it possible for the Coil Clean ILs to be easily tied to building automation systems.

# COIL SECTION

#### **Electric Heater**



Heat Recovery







#### Construction

Electric heaters are available wide range of capacity (KW) and steps. Electric heaters frame are made of GI. As a standard heater RA provided open type finned heater construction from 80/20 nickel chrome resistance via anti thermal shock, moisture resistant steatite free floating holding ceramics. Electric heater provided in a separate section.

#### Construction

Fins are aluminum as a standard. Upon request, marine aluminum, industrial precoated epoxy or hydrophilic fins can be also used. Frame can be manufactured from special aluminum profile covers can be manufactured from galvanized sheet metal or aluminum.

Cross-flow heat recovery plate exchangers can be connected in series to increase the efficiency



www.EcoCooler.com.tr

### CONTROL EQUIPMENT

To have a great control over running cost, ECO COOLER AHUs are fitted with low noise, high output, Space saving, less weight, long bearing life induction motors. VFD is used to drive the fan at designed RPM to create the required air flow. Fans are driven by motors with V-Belt drive.

#### **VFD Drive Inverter**



#### Construction

ECO COOLER AHUS are compatible to fit with variable-frequency drive (VFD). Controlling Fan volume with a VFD offers the user low noise generation and high energy efficiency when regulating flow to within 80 percentage of design or less. A variable-frequency drive is a system for controlling the rotational speed of an AC electric motor by controlling the frequency of the electrical power supplied to the motor. A variable frequency drive is a specific type of adjustable-speed drive.

#### **Control Valve**



#### Construction

Three-way and Two-way valves can be provided as an optional feature in AHUs.

Control valves are factory fitted on the headers of the coil heat exchangers and located inside the casing of AHUs.

Control valves are fitted with actuator controls to precisely control the required flow across the coil. Valves are available in Brass up to specific diameter of pipes and the cast iron.

# CONTROL EQUIPMENT

#### **Damper Actuator**



#### Construction

Actuators are designed for long lasting, reliable and quiet operation of air control dampers. All actuators feature a universal self centering mounting clamp and anti-rotation strap as well as durable brushless DC motor technology and easy manual positioning. Actuators provide high quality, cost effective solution for all environments, with a complete selection for high humidity, wide temperature extremes and outdoor applications, without requiring costly additional enclosures.

#### Steam Humidifier



#### Construction

Air handling units can be equipped with a selfcontained humidifier, which is electronically controlled to sense and control the humidity. The steam is generated in a polypropylene cylinder mounted onto the outside of the humidifier section within a special enclosure. A stainless steel distributor suitable in length passes through the unit casing to inject steam in the air stream to reach the needed humidity conditions.



# **TYPICAL WIRING DIAGRAM**





www.ecocooler.com.tr



www.EcoCooler.com.tr